

AMF

BREAD BELT ROUNDER



- **Precision Belt Rounding Without Dusting Flour or Doubles**
- **Excellent Rounding Quality for a Wide Range of Dough Piece Sizes and Types**

FEATURES & BENEFITS

High Speed Precision Rounding

- Uses an FDA approved poly-slick rounding belt that prevents dough sticking
- Produces higher quantities of precisely rounded dough pieces while virtually eliminating scraps and doubling

AMF Compatibility and Versatility

- Compliments the AMF Advanced Dough Divider (ADD) and is easily controlled by the ADD's operator control station
- Efficient design with few moving parts for reduced maintenance cost
- Processes dough pieces ranging from 9 oz. (255 g) to 38 oz. (1077 g)* in single, dual, and triple channel configurations

Heavy-Duty Construction and Efficient Design

- Rigid laser cut stainless steel frame
- Eurodrive gearmotor with AC frequency drive speed control for versatility and reliability
- Increased operating speeds up to 390 cuts per minute can increase your hourly production yield
- Wide range of flexibility to handle multiple dough types, including frozen doughs and pizza crust

* With optional adjustable curvature bars

MECHANICAL FEATURES

- Durable stainless steel frame
- "C" frame design for easy rounder belt removal
- Poly-slick rounder belt to prevent dough sticking and belt stretching
- Stainless steel one-piece rounder pulleys designed for consistent belt tracking
- Hinged rounder bars for easy cleaning and maintenance
- Adjustable poly belt scraper with stainless steel catch pan
- Direct drive with class F insulated Eurodrive gearmotor with AC speed control for dependability, long life, and 94% mechanical efficiency
- Grooved UHMW rounder bars sized to meet your specific product range



Grooved UHMW Rounder Bars



OPTIONS

- Chilled rounder bed
- Inverter other than Toshiba
- Adjustable curvature of both height and width of rounding tunnels gives optimum results while accommodating a wide range of dough piece sizes
- S.A.E. tool kit

SPECIFICATIONS

	Scaling Range	Speed Range (max. pcs/hr.)	Approximate Shipping Weight
Single Channel	9 oz. - 38 oz. (255 g - 1077 g)	12,000	3,100 lb. (1406 kg)
Dual Channel	9 oz. - 38 oz. (255 g - 1077 g)	18,000	3,200 lb. (1452 kg)
Triple Channel	9 oz. - 38 oz. (255 g - 1077 g)	18,000	3,400 lb. (1542 kg)

Electrical Requirements:

Main Power - 11 KVA


Control Power - 24 VDC/120 VAC

Approximate Shipping Dimensions:

169" x 68" x 51"

(4293 mm x 1727 mm x 1295 mm)

DIMENSIONAL DRAWING



Headquarters:

2115 W. Laburnum Ave.
 Richmond, Virginia 23227
Tel: 1-800-225-3771
or 1-804-355-7961
Fax: 1-804-342-9724
sales@amfbakery.com

Europe Office:

6 The Sidings
 Station Road, Guiseley
 Leeds LS20 8BX, England
Tel: 44-1943-875703
Fax: 44-1943-871806
sales-europe@amfbakery.com

Asia Office:

Room 15-2, A-Building
 Thunis Dev. Building
 No.11 Hui Xin East St.
 Chaoyang District
 Beijing, China 100029
Tel: 86-10-64823613
Fax: 86-10-64934259
sales-asia@amfbakery.com

FOR MORE INFORMATION PLEASE CALL YOUR ACCOUNT MANAGER OR

1-800-BAKERS-1
www.amfbakery.com

AMF's focus on continuous improvement may result in changes to machinery specifications without notice.